



# The 1150 Ultra

## New Construction Double Hung Window

### We have thought of everything

We listened to what our customers have asked for in a quality new construction window and we have delivered. The 1150 ULTRA is packed with over 30 high-end features that you will not find in any other window. The 1150 ULTRA upholds our tradition of providing our customers the best possible window money can buy.

The 1100 With Solarban® 70 XL, the best choice for energy-efficient glass is very clear.



With an unparalleled combination of visible light transmittance, energy-saving solar control and a clear glass appearance, Solarban® 70 XL Solar Control Low-E Glass represents the

most dramatic advance in window glass in more than a decade.

This revolutionary Solar Control Low-E glass allows homeowners to cut summer cooling costs by as much as 25% while enjoying all the benefits of abundant interior sunlight and a clear, color-neutral glass appearance.

**SUPERSEAL**

Windows & Doors

**(888) NEW VINYL • [www.supersealwindows.com](http://www.supersealwindows.com)**

# 1150 ULTRA DOUBLE HUNG



Reverse brickmold frame and integral nailing flange

The UltraTech™ Auto Tilt series hardware provides the homeowner with a clean, low profile lock system. The tilt latch assembly is concealed within the extrusion to provide a modern style window. The innovative locking system combines the lock, tilt and clean-on-demand options into one flush lock.

Make Yourself Comfortable



Windows & Doors



**COLORS:**

- MODERN EUROPEAN WHITE
- CUSTOM

**STYLES:**

**GRID PATTERNS:** **GRID PROFILES:**

**DP 50\*** **ENERGY STAR**

**30%**  
The 1150-Ultra Performs 30% Better Than the Average ENERGYSTAR® Window



## Features

- 1" Solarban® 70XL Double Strength Low-E Glass
- SustainaView™ Super Spacer® Glazing Technology
- Constant force stainless steel balance hardware system
- 25 Year Glass Breakage Warranty
- Foam filled main frame
- Jamb jacks for ease of installation
- UltraTech™ auto-tilt window locking system
- Slider and picture units available in matching reverse brickmold frame
- Modern European white colored pvc profile
- Fully welded sash system with contour bevel
- Impost design for all multiple twins and triples (field H mullions are available for non - factory mullied units)
- Fully welded main frame with 10 degree sloped sill

## Options:

- Factory–Applied Extension Jamb: 4-9/16" or 6-9/16" Primed Wood
- Hurricane Impact Package
- Triple insulated glass
- Custom color options
- Grid System: flat/contour and decorative grid
- Bay and Bow system
- Krypton Gas

## Egress Size:

R.O. / Call Size:	36 X 66
Tip to Tip:	35 1/2 X 65 1/2
Egress Formula:	Double Hung: (W-4.5) * (H/2-6.25) /144 Slider: (W/2- 5.375) * (H- 4.25) /144

\* Please refer to structural test report for DP rating sizing criteria.

## Testing Data:

Visit [www.supersealwindows.com](http://www.supersealwindows.com) to view the most recent Energy Rating and Structural Performance Data.