




# 1250 Single Hung

## New Construction Window

### Versatility, Strength and Low Sound Transmittance

The Superseal Series 1250's superior structural integrity and design makes this window an excellent choice for residential and lite commercial projects.

If keeping the sounds of a busy street or noisy neighborhood from invading a home or office is a concern, then the 1250's high rating for sound transmittance, makes this unit the right choice again.



Cardinal LoE<sup>2</sup>-272®  
Ultra Energy Efficient Low E Glass

Whether it is 20 below or 110 in the shade, you can bring year-round comfort to your home with Cardinal CG Company's LoE<sup>2</sup>-272® glass. In winter, LoE<sup>2</sup>-272 reflects heat back into the room. In summer, it rejects the sun's heat and damaging solar rays. Additionally, it is the clearest, highest performing glass you can buy - without haze or a bluish cast.

**SUPERSEAL**

Windows & Doors

(888) NEW VINYL • [www.supersealwindows.com](http://www.supersealwindows.com)

# 1250 Single Hung Window



Make Yourself Comfortable

## SUPERSEAL


Windows & Doors



**COLORS:**



**STYLES:**



**GRID PATTERNS:**



**GRID PROFILES:**



**Features**

- 3/4" "Warm Edge" Insulating Glass
- Integral Star Punched Nailing Flange
- Welded Sash and Frame
- Tilt-n-Sash
- Screen Standard
- Fin-Seal Weather-stripping
- Load Window Capacity
- Continuous Head And Sill For Multiple Units
- DP-50 Rating
- NFRC Certified
- Double Locks (On Units Over 28" In Width)

**Options:**

- Factory-Applied Extension Jamb: 4-9/16" or 6-9/16" Primed Wood
- Custom color options
- STC (Sound Transmittance Classification) of 32 or higher with special glass options
- Colonial/Contour grids (see page 26)
- SDL (simulated divided lites) Replicates historical appearance

**Glass Options**

- Argon Gas
- Bronze Tint Glass
- Frosted Wire
- Grey Tint Glass
- Lexan / Laminated
- Low-E
- Low-E Tempered
- Plain Frosted
- Stucco Panel
- Tempered
- Wire Glass
- Krypton Gas

**Egress Size:**

R.O. / Call Size:	36 X 60
Tip to Tip:	35 1/2 X 59 1/2
Egress Formula:	Single Hung: ( W- 4.5)* (H/2-5) / 144 Slider: (W/2-4.062)* (H-5) / 144

\* Please refer to structural test report for DP rating sizing criteria.

**Testing Data:**

Visit [www.supersealwindows.com](http://www.supersealwindows.com) to view the most recent Energy Rating and Structural Performance Data.