




Windows & Doors

1250J Single Hung New Construction Window

1250 J-Channel Designed for Swift Siding Installations.

The 1250J (J for integral J channel) packs the same muscle as our standard 1250 window with the added feature of an integral J channel designed for siding and 1" casing applications. Homeowners will love the cosmetic appeal of a premium wood window with the maintenance free energy efficiency of a Superseal vinyl window. A true-slope sill and the built in J-channel, provides a clean finished look for siding applications that adds plenty of curb appeal to any home. For twin and triple units, a continuous head and sill impost design add structural integrity to assure a problem free installation.

If keeping the sounds of a busy street or noisy neighborhood from invading a home or office is a concern, then the 1250J's high rating for sound transmittance, makes this unit the right choice again.



Cardinal LoE²-272®
Ultra Energy Efficient Low E Glass

Whether it is 20 below or 110 in the shade, you can bring year-round comfort to your home with Cardinal CG Company's LoE²-272® glass. In winter, LoE²-272 reflects heat back into the room. In summer, it rejects the sun's heat and damaging solar rays. Additionally, it is the clearest, highest performing glass you can buy - without haze or a bluish cast.

(888) NEW VINYL • www.supersealwindows.com

1250J Single Hung Window



Make Yourself Comfortable

SUPERSEAL


Windows & Doors



COLORS:



STYLES:



GRID PATTERNS:



GRID PROFILES:



Features

- Integral J-Channel
- 3/4" "Warm Edge" Insulating Glass
- Integral Star Punched Nailing Flange
- Welded Sash and Frame
- Tilt-n-Sash
- Screen Standard
- Fin-Seal Weather-stripping
- Load Window Capacity For Stock Programs
- Continuous Head And Sill For Multiple Units
- C-60 commercial rating
- DP-50 Rating
- NFRC Certified
- Double Locks (On Units Over 28" In Width)

Options:

- Factory-Applied Extension Jamb: 4-9/16" or 6-9/16" Primed Wood
- Custom color options
- STC (Sound Transmittance Classification) of 32 or higher with special glass options
- Colonial/Contour grids
- SDL (simulated divided lites) Replicates historical appearance

Glass Options

- Argon Gas
- Bronze Tint Glass
- Frosted Wire
- Grey Tint Glass
- Lexan / Laminated
- Low-E
- Low-E Tempered
- Plain Frosted
- Stucco Panel
- Tempered
- Wire Glass
- Krypton Gas

Egress Size:

R.O. / Call Size:	36 X 60
Tip to Tip:	35 1/2 X 59 1/2
Egress Formula:	Single Hung: (W- 4.5) * (H/2-5) / 144 Slider: (W/2-4.062) * (H-5) / 144

* Please refer to structural test report for DP rating sizing criteria.

Testing Data:

Visit www.supersealwindows.com to view the most recent Energy Rating and Structural Performance Data.