



Windows & Doors



COLORS:
 WHITE BEIGE CUSTOM

STYLES:

GRID PATTERNS: **GRID PROFILES:**

Features

- Brickmould Frame
- 3/4" "Warm Edge" Insulating Glass
- Welded Sash and Frame
- Integral Star-Punched Nailing Fin And J Channel
- Tilt-n-Sash
- Sloped Sill
- Weather-Stripped Interlock
- Double Locks (On Units Over 28" In Width)
- Full Fiberglass Screen
- Block And Tackle Balance System With Lift Out Sash Design
- Continuous Head And Sill For Multiple Units
- DP-50 Rating
- Field Mull Capability
- NFRC Certified

Options:

- Factory-Applied Extension Jamb: 4-9/16" or 6-9/16" Primed Wood
- Colonial/Contour grids
- Custom paint options
- SDL (simulated divided lites) Replicates historical appearance

1850J New Construction Double Hung Window. Consistently Reliable.

The Series 1850J new construction double hung window offers high-quality craftsmanship at an affordable price. Loaded with features and a crisp, classic look.

The 1850J (J for integral J-Channel) has the same features as our 1850B but in a J-Channel design. The 1850J is designed for siding and casing applications. Homeowners will love the cosmetic appeal of a premium wood window with the maintenance free energy efficiency of a Superseal vinyl window. The 1850J will give home buyers enhanced beauty for years to come and a substantial return on their investment with superior energy efficiency.

Glass Options

- Argon Gas
- Bronze Tint Glass
- Frosted Wire
- Grey Tint Glass
- Lexan / Laminated
- Low-E
- Low-E Tempered
- Plain Frosted
- Stucco Panel
- Tempered
- Wire Glass
- Krypton Gas

Egress Size:

R.O. / Call Size:	36 x 60
Tip to Tip:	35 1/2" x 59 1/2"
Egress Formula:	Double Hung: (W -4.125) * (H/2- 4.75) /144
	Double Hung: (W- 4.125) * (H/2-3.5) /144 (used in a 3050 and 3046-A only)
	Slider: (W/2- 4.582) * (H-4.75) /144

* Please refer to structural test report for DP rating sizing criteria.

Testing Data:

Visit www.supersealwindows.com to view the most recent Energy Rating and Structural Performance Data.