

800/850 Sliding Patio Door For Remodeling or New Construction

For a lifetime of smooth maintenance-free use

The 1100 Ultra. Leads the way in efficiency, value and premium features.

The Series 800/850 Vinyl Patio Door for replacement and new construction packs a powerful DP-45* rating, is made of sturdy, multi-chambered vinyl and has a self-lubricating vinyl frame and adjustable tandem bearings. These features ensure that the door always operates smoothly and is virtually maintenance-free, giving you long lasting performance.

The 800/850 is NFRC certified to qualify for the 2009 Stimulus Bill tax credit, up to \$1,500 per home!



The 800/850 With Solarban® 70 XL, the best choice for energy-efficient glass is very clear.



With an unparalleled combination of

visible light transmittance, energy-saving solar control and a clear glass appearance, Solarban® 70 XL Solar Control Low-E Glass represents the most dramatic advance in window glass in more than a decade.

This revolutionary Solar Control Low-E glass allows homeowners to cut summer cooling costs by as much as 25% while enjoying all the benefits of abundant interior sunlight and a clear, color-neutral glass appearance.



SUPERSEAL
Windows & Doors

www.supersealwindows.com
1 (888) NEW-VINYL

800/850 Sliding Patio Door



Continuous Frame Design allows for transom and door to be constructed into one frame


V-GROVED GLASS SHOWN



COLORS:



STYLES:



GRID PATTERNS:

GRID PROFILES:



TESTING CERTIFICATIONS:



Features:

- 1" Tempered Insulating Glass
- SustainaView™ Super Spacer® Glazing Technology
- Aluminum Reinforced Hardware Rail
- Aluminum extruded Heavy-Duty Screen
- Fully Assembled Welded Sash & Frame
- Continuous Frame Design allows for transom and door to be constructed into one frame
- Standard Hardware Included
- NFRC Certified
- DP-45 Rating

Options:

- Solarban® 70XL Low-E Glass
- *V-Groove Glass
- Solid Brass Hardware With Key Lock
- Handicapped Accessible 32" Clear Opening Door.
- Handicapped Accessible Interior And Exterior Ramp Kit
- Custom Colors
- Grids
- Stainless Steel Hardware

Size Options:

	Frame	Tip to Tip	Panels
Left or Right Hand Operation	5'0" x 6'8"	59-1/2" x 79-1/2"	2
	6'0" x 6'8"	71-1/2" x 79-1/2"	2
	8'0" x 6'8"	95-1/2" x 79-1/2"	2
Left, Right or Center Operation	9'0" x 6'8"	106-3/4" x 79-1/2"	3
	12'0" x 6'8"	143" x 79-1/2"	3
	French Sliding	10'0" x 6'8"	117-1/2" x 79-1/2"
12'0" x 6'8"		141-1/2" x 79-1/2"	4

Energy Rating Factors:

U-Value	Solar Heat Gain	Visible Light Transmittance	Condensation Resistance
Standard With Clear Tempered Insulated Glass			
0.47	0.66	0.68	42.60
With Optional Tempered Solarban® 70XL Double Strength Low-E & Argon Gas			
0.29	0.23	0.54	55.00

*ORDERS PLACED WITH V-GROOVE GLASS COME STANDARD WITH: Low-E Glass, Argon Gas, Brass Exterior Hardware & Key Lock.

* Please refer to structural test report for DP rating sizing criteria. Energy rating factors for other glazing options can be found in the NFRC Certified Products Database at www.NFRC.org

Make Yourself Comfortable



Windows & Doors